




# ASAHI BEARING FORGE DE CORP.



VA201



2Z/VA201



2Z/VA208



2Z/VA228

## SKF High Temperature Bearing 6211-2z/Va201 for SKF High Temperature Bearing

Bearing No. 6211-2z/Va201

6211-2z/Va201 Bearing 2D drawings and 3D CAD models

Size	55x100x21 mm
Bore Diameter	55 mm
Outer Diameter	100 mm
Width	21 mm
d	55 mm
D	100 mm
B	21 mm
C	21 mm
d1	69 mm
r1 min.	1,5 mm
r2 min.	1,5 mm
D2	89,4 mm
Weight	0,61 Kg
Temperature -	30 to +250 °
Basic static load rating (C0)	29 kN
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	7316571587981
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No



## ASAHI BEARING FORGE DE CORP.

Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	55MM Bore; 100MM Outside Diameter; 21MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Fe
Other Features	Deep Groove   Extreme Temperature Variant
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / LBS	0.64
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.827 Inch   21 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
Bore	2.165 Inch   55 Millimeter
d <sub>1</sub>	69.06 mm
D <sub>2</sub>	89.4 mm
r <sub>1,2</sub> min.	1.5 mm
d <sub>a</sub> min.	64 mm
d <sub>a</sub> max.	69 mm
D <sub>a</sub> max.	91 mm



## ASAHI BEARING FORGE DE CORP.

$r_a$ max.	1.5 mm
Basic dynamic load rating C	46.2 kN
Basic static load rating $C_0$	29 kN
Limiting speed	50 r/min
Limiting temperature T max.	250 ° C
Mass bearing	0.64 kg